



Data Sheet CODESYS J1939 Manager SL

The CODESYS J1939 Manager SL enables a controller to act as a J1939 ECU that is programmable with the CODESYS Development System.

Product description

CODESYS J1939 SL implements J1939 functionality on a CODESYS controller and enables receiving and sending of parameter groups. The fieldbus stack can be downloaded dynamically together with the IEC application. CODESYS J1939 editor pages offer an easy way to parameterize the J1939 communication.

More information

General information

Manufacturer:

3S-Smart Software Solutions GmbH
 Memminger Strasse 151
 87439 Kempten
 Germany

Support:

<https://support.codesys.com>

Item:

CODESYS J1939 Manager SL

Item number:

2303000022

Sales:

CODESYS Store

<https://store.codesys.com>

Included in delivery:

- License key

System requirements and restrictions

Programming System	CODESYS Development System V3.5.5.0 or higher
Runtime System	CODESYS Control V3.5.5.0 or higher
Supported Platforms/ Devices	Note: Use the project "Device Reader" to find out the supported features of your device. "Device Reader" is available for free in the CODESYS Store.
Additional Requirements	CODESYS Control runtime system on the device with component "CmpCAACanL2"
Restrictions	-
Licensing	License activation optional on CODESYS Key or Soft Key (Soft Key: free of charge component of CODESYS Controls)
Required Accessories	Optional: CODESYS Key

Note: Not all CODESYS features are available in all territories. For more information on geographic restrictions, please contact sales@codesys.com.

Note: Technical specifications are subject to change. Errors and omissions excepted. The content of the current online version of this document applies.